

Cassette Units



Compact (600 x 600) 4 Way Cassette

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MMU-AP0071MH	0.8	2.2	2.5	1Ph (5A)	575	268	575	17	28-32-36	105-128-153	Price & dimensions exclude grille. Lift pump fitted as standard (625mm from outlet).
MMU-AP0091MH	1	2.8	3.2	1Ph (5A)	575	268	575	17	28-33-37	105-130-158	
MMU-AP0121MH	1.25	3.6	4.0	1Ph (5A)	575	268	575	17	29-33-37	112-140-165	
MMU-AP0151MH	1.7	4.5	5.0	1Ph (5A)	575	268	575	17	30-35-40	130-153-183	
MMU-AP0181MH	2	5.6	6.3	1Ph (5A)	575	268	575	17	34-39-44	145-178-212	
RBC-UM11PG(W)E	-	-	-	-	700	27	700	3	-	-	Grille for all of above



4 Way Cassette

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MMU-AP0092H	1	2.8	3.2	1Ph (5A)	840	256	840	18	27-29-30	189-203-222	Price & dimensions exclude grille.
MMU-AP0122H	1.25	3.6	4.0	1Ph (5A)	840	256	840	18	27-29-30	189-203-222	
MMU-AP0152H	1.7	4.5	5.0	1Ph (5A)	840	256	840	20	27-29-31	219-231-258	
MMU-AP0182H	2	5.6	6.3	1Ph (5A)	840	256	840	20	27-29-32	222-256-292	
MMU-AP0242H	2.5	7.1	8.0	1Ph (5A)	840	256	840	20	28-31-35	222-256-358	
MMU-AP0272H	3	8.0	9.0	1Ph (5A)	840	256	840	20	28-31-35	222-256-358	
MMU-AP0302H	3.2	9.0	10.0	1Ph (5A)	840	256	840	20	30-33-38	236-306-367	
MMU-AP0362H	4	11.2	12.5	1Ph (5A)	840	319	840	25	32-38-43	297-397-547	
MMU-AP0482H	5	14.0	16.0	1Ph (5A)	840	319	840	25	33-38-46	314-397-592	
MMU-AP0562H	6	16.0	18.0	1Ph (5A)	840	319	840	25	33-40-46	342-422-592	
RBC-U31PG(W)E	-	-	-	-	950	30	950	4.0	-	-	Grille for all of above



2 Way Cassette

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MMU-AP0071WH	0.8	2.2	2.5	1Ph (5A)	830	398	550	33	30-32-34	125-142-158	Price & dimensions exclude grille. Lift pump fitted as standard (160mm from outlet).
MMU-AP0091WH	1	2.8	3.2	1Ph (5A)	830	398	550	33	30-32-34	125-142-158	
MMU-AP0121WH	1.25	3.6	4.0	1Ph (5A)	830	398	550	33	30-32-34	125-142-158	
MMU-AP0151WH	1.7	4.5	5.0	1Ph (5A)	1350	398	550	44	30-33-35	167-195-217	
MMU-AP0181WH	2	5.6	6.3	1Ph (5A)	1350	398	550	44	30-33-35	167-195-217	
MMU-AP0241WH	2.5	7.1	8.0	1Ph (5A)	1350	398	550	48	33-35-38	200-267-317	
MMU-AP0271WH	3	8.0	9.0	1Ph (5A)	1350	398	550	48	33-35-38	200-267-317	
MMU-AP0301WH	3.2	9.0	10.0	1Ph (5A)	1350	398	550	48	34-37-40	267-317-350	
RBC-UW136PG	-	-	-	-	1000	8	650	8	-	-	Grille for 0071-0121 units
RBC-UW266PG	-	-	-	-	1520	8	650	11	-	-	Grille for 0151-0301 units



1 Way Cassette

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MMU-AP0071YH	0.8	2.2	2.5	1Ph (5A)	850	235	400	22	34-39-42	117-133-150	Price & dimensions exclude grille. Lift pump fitted as standard (71-121 = 150mm, 152-242 = 695mm from outlet).
MMU-AP0091YH	1	2.8	3.2	1Ph (5A)	850	235	400	22	34-39-42	117-133-150	
MMU-AP0121YH	1.25	3.6	4.0	1Ph (5A)	850	235	400	22	34-39-42	117-133-150	
MMU-AP0152SH	1.7	4.5	5.0	1Ph (5A)	1000	200	710	21	35-39-42	183-200-217	
MMU-AP0182SH	2	5.6	6.3	1Ph (5A)	1000	200	710	21	35-39-42	183-200-217	
MMU-AP0242SH	2.5	7.1	8.0	1Ph (5A)	1000	200	710	22	37-41-43	283-317-333	
RBC-UY135PG	-	-	-	-	1050	18	470	3.5	-	-	Grille for 0071 - 0121 units
RBC-US21PGE	-	-	-	-	1230	20	800	5.5	-	-	Grille for 0152 - 0242 units

AMP Air Conditioning Limited is an Authorised Toshiba Air Conditioning Distributor

Ducted Units



Low Height Ducted

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)		Airflow Rate (l/s)	Static Pressure (Pa)	Notes
		Cooling	Heating		Width	Height	Depth		Lower Air Inlet	Rear Air Inlet			
MMD-AP0071SPH	0.8	2.2	2.5	1Ph (5A)	845	210	645	22	30-33-36	24-26-28	111-131-150	10-20-35-49	Lower air inlet as standard (rear air inlet available). Air filter and lift pump fitted as standard (685mm from outlet).
MMD-AP0091SPH	1	2.8	3.2	1Ph (5A)	845	210	645	22	30-33-36	24-26-28	111-131-150	10-20-35-49	
MMD-AP0121SPH	1.25	3.6	4.0	1Ph (5A)	845	210	645	22	32-35-38	25-27-29	125-145-167	10-20-35-49	
MMD-AP0151SPH	1.7	4.5	5.0	1Ph (5A)	845	210	645	23	33-36-39	28-30-32	145-167-192	10-20-35-49	
MMD-AP0181SPH	2	5.6	6.3	1Ph (5A)	845	210	645	23	36-38-40	29-31-33	161-189-217	10-20-35-49	



Standard Ducted

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Static Pressure (Pa)	Notes
		Cooling	Heating		Width	Height	Depth					
MMD-AP0071BH	0.8	2.2	2.5	1Ph (5A)	550	320	800	28	26-28-30	95-117-133	40-100	Rear air inlet as standard. Air filter and lift pump (270mm) fitted as standard.
MMD-AP0091BH	1	2.8	3.2	1Ph (5A)	550	320	800	28	26-28-30	95-117-133	40-100	
MMD-AP0121BH	1.25	3.6	4.0	1Ph (5A)	550	320	800	28	27-29-31	111-136-158	40-100	
MMD-AP0151BH	1.7	4.5	5.0	1Ph (5A)	700	320	800	32	27-29-31	133-150-181	40-100	
MMD-AP0181BH	2	5.6	6.3	1Ph (5A)	700	320	800	32	28-30-32	150-183-217	40-100	
MMD-AP0241BH	2.5	7.1	8.0	1Ph (5A)	1000	320	800	43	29-31-33	242-275-317	40-100	
MMD-AP0271BH	3	8.0	9.0	1Ph (5A)	1000	320	800	43	29-31-33	242-275-317	40-100	
MMD-AP0301BH	3.2	9.0	10.0	1Ph (5A)	1000	320	800	43	29-32-34	242-300-350	40-100	
MMD-AP0361BH	4	11.2	12.5	1Ph (5A)	1350	320	800	55	32-34-36	333-392-450	40-100	
MMD-AP0481BH	5	14.0	16.0	1Ph (5A)	1350	320	800	55	32-36-38	414-475-550	40-100	
MMD-AP0561BH	6	16.0	18.0	1Ph (5A)	1350	320	800	55	32-36-38	414-475-550	40-100	



High Static Ducted

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Static Pressure (Pa)	Notes
		Cooling	Heating		Width	Height	Depth					
MMD-AP0181H	2	5.6	6.3	1Ph (5A)	850	380	660	50	33-35-37	200-250-300	69-137-196	Unit does not come with filter
MMD-AP0241H	2.5	7.1	8.0	1Ph (5A)	850	380	660	52	36-38-40	295-367-439	69-137-196	
MMD-AP0271H	3	8.0	9.0	1Ph (5A)	850	380	660	52	36-38-40	295-367-439	69-137-196	
MMD-AP0361H	4	11.2	12.5	1Ph (5A)	850	380	660	56	36-38-40	356-445-533	69-137-196	
MMD-AP0481H	5	14.0	16.0	1Ph (5A)	1200	380	660	67	36-38-40	467-583-700	69-137-196	
MMD-AP0721H	8	22.4	25.0	1Ph (5A)	1380	470	1250	150	45-47-49	800-1000-1200	69-137-196	
MMD-AP0961H	10	28.0	31.5	1Ph (5A)	1380	470	1250	150	46-48-50	933-1167-1400	69-137-196	

Floor Standing Units



Floor Standing Chassis

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MML-AP0071BH	0.8	2.2	2.5	1Ph (5A)	745	600	220	21	32-34-36	83-111-128	Top or front discharge
MML-AP0091BH	1	2.8	3.2	1Ph (5A)	745	600	220	21	32-34-36	83-111-128	
MML-AP0121BH	1.25	3.6	4.0	1Ph (5A)	745	600	220	21	32-34-36	83-111-128	
MML-AP0151BH	1.7	4.5	5.0	1Ph (5A)	1045	600	220	29	32-34-36	136-167-206	
MML-AP0181BH	2	5.6	6.3	1Ph (5A)	1045	600	220	29	32-34-36	136-167-206	
MML-AP0241BH	2.5	7.1	8.0	1Ph (5A)	1045	600	220	29	33-37-42	178-220-264	



Floor Standing Cabinet

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MML-AP0071H	0.8	2.2	2.5	1Ph (5A)	950	630	230	37	35-37-39	100-117-133	Top or front discharge
MML-AP0091H	1	2.8	3.2	1Ph (5A)	950	630	230	37	35-37-39	100-117-133	
MML-AP0121H	1.25	3.6	4.0	1Ph (5A)	950	630	230	37	38-41-45	181-217-250	
MML-AP0151H	1.7	4.5	5.0	1Ph (5A)	950	630	230	37	38-41-45	181-217-250	
MML-AP0181H	2	5.6	6.3	1Ph (5A)	950	630	230	40	39-44-49	217-258-300	
MML-AP0241H	2.5	7.1	8.0	1Ph (5A)	950	630	230	40	39-44-49	217-258-300	



Floor Standing Tall

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MMF-AP0151H	1.7	4.5	5.0	1Ph (5A)	600	1750	210	48	38-43-46	183-217-250	
MMF-AP0181H	2	5.6	6.3	1Ph (5A)	600	1750	210	48	38-43-46	183-217-250	
MMF-AP0241H	2.5	7.1	8.0	1Ph (5A)	600	1750	210	49	40-45-49	233-283-333	
MMF-AP0271H	3	8.0	9.0	1Ph (5A)	600	1750	210	49	40-45-49	233-283-333	
MMF-AP0361H	4	11.2	12.5	1Ph (5A)	600	1750	390	65	44-48-51	383-467-533	
MMF-AP0481H	5	14.0	16.0	1Ph (5A)	600	1750	390	65	46-50-54	433-517-600	
MMF-AP0561H	6	16.0	18.0	1Ph (5A)	600	1750	390	65	46-50-54	433-517-600	

High Wall & Ceiling Suspended Units



High Wall

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MMK-AP0073H	0.8	2.2	2.5	1Ph (5A)	1050	320	228	15	28-31-35	109-125-158	
MMK-AP0093H	1	2.8	3.2	1Ph (5A)	1050	320	228	15	28-32-37	109-133-167	
MMK-AP0123H	1.25	3.6	4.0	1Ph (5A)	1050	320	228	15	28-32-37	109-133-167	
MMK-AP0153H	1.7	4.5	5.0	1Ph (5A)	1050	320	228	15	33-36-41	150-183-233	
MMK-AP0183H	2	5.6	6.3	1Ph (5A)	1050	320	228	15	33-36-41	150-183-233	
MMK-AP0243H	2.5	7.1	8.0	1Ph (5A)	1050	320	228	15	34-39-46	158-208-283	



Ceiling Suspended

Model	Capacity Code	Nominal Capacity (kW)		Power Supply	Dimensions (mm)			Net Weight (kg)	Sound Pressure Level (dBA)	Airflow Rate (l/s)	Notes
		Cooling	Heating		Width	Height	Depth				
MMC-AP0151H	1.7	4.5	5.0	1Ph (5A)	910	210	680	22	30-32-35	150-167-200	
MMC-AP0181H	2	5.6	6.3	1Ph (5A)	910	210	680	22	30-33-36	150-183-217	
MMC-AP0241H	2.5	7.1	8.0	1Ph (5A)	1180	210	680	26	33-36-38	233-250-308	
MMC-AP0271H	3	8.0	9.0	1Ph (5A)	1180	210	680	26	33-36-38	233-250-308	
MMC-AP0361H	4	11.2	12.5	1Ph (5A)	1595	210	680	34	35-38-41	333-383-458	
MMC-AP0481H	5	14.0	16.0	1Ph (5A)	1595	210	680	34	37-40-43	367-433-500	

Indoor Unit Capacity Codes & Flow Selector Units

Indoor Type	Nom Cooling Capacity (kW)	Nom Heating Capacity (kW)	Capacity Code	Flow Selector Unit (SHRM Only)
0071	2.2	2.5	0.8	RBM-Y1122FE
0091	2.8	3.2	1	RBM-Y1122FE
0121	3.6	4.0	1.25	RBM-Y1122FE
0151	4.5	5.0	1.7	RBM-Y1122FE
0181	5.6	6.3	2	RBM-Y1122FE
0241	7.1	8.0	2.5	RBM-Y1122FE
0271	8.0	9.0	3	RBM-Y1122FE
0301	9.0	10.0	3.2	RBM-Y1122FE
0361	1.2	12.5	4	RBM-Y1802FE
0481	14.0	16.0	5	RBM-Y1802FE
0561	16.0	18.0	6	RBM-Y1802FE
0721	22.4	21.0	8	RBM-Y1802FE
0961	28.0	31.5	10	RBM-Y1802FE